

Rec'd PCT/PTO 08 APR 2005

CI/GB 2003 / 004433

#2



INVESTOR IN PEOPLE

The Patent Office
Concept House
Cardiff Road

Newport
South Wales
NP10 80Q

REC'D 21 NOV 2003

WIPO PCT

PRIORITY DOCUMENT

SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed

P. Mahoney

Dated

28 October 2003

**The
Patent
Office**

THE PATENT OFFICE
12 OCT 2002
NEWPORT

1/77

request for grant of a patent

*the notes on the back of this form. You can also get
planatory leaflet from the Patent Office to help
fill in this form)*

The Patent Office

Cardiff Road
Newport
Gwent NP9 1RH

Your reference

11112P3 GB/AK

12 OCT 2002

Patent application number
(The Patent Office will fill in this part)

0223839.2

15OCT02 E755656-1 D02903
P01/7700 0.00-0223839.2

Full name, address and postcode of the or of
each applicant (*underline all surnames*)

Reckitt Benckiser Inc
1655 Valley Road
Wayne
New Jersey 07474
UNITED STATES OF AMERICA

Patents ADP number (*if you know it*)

07852247001

If the applicant is a corporate body, give the
country/state of its incorporation

Delaware

Title of the invention

Improvements In and To Organic Compositions

Name of your agent (*if you have one*)

John Crawford McKnight
Reckitt Benckiser plc
Group Patents Department
Dansom Lane
HULL
HU8 7DS
UNITED KINGDOM

"Address for service" in the United Kingdom
to which all correspondence should be sent
(*including the postcode*)

Patents ADP number (*if you know it*)

07799521001

If you are declaring priority from one or more
earlier patent applications, give the country
and the date of filing of the or of each of these
earlier applications and (*if you know it*) the or
each application number

Country

Priority application number
(*if you know it*)

Date of filing
(*day / month / year*)

If this application is divided or otherwise
derived from an earlier UK application,
give the number and the filing date of
the earlier application

Number of earlier application
(*day / month / year*)

Date of filing
(*day / month / year*)

3. Is a statement of inventorship and of right
to grant of a patent required in support of
this request? (*Answer 'Yes' if:*

Yes

- a) any applicant named in part 3 is not an inventor, or
 - b) there is an inventor who is not named as an
applicant, or
 - c) any named applicant is a corporate body.
- See note (d))

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description	11	/
Claim(s)	2	/
Abstract	1	/ RN
Drawing(s)	---	

10. If you are also filing any of the following, state how many against each item.

Priority documents
Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for preliminary examination and search (Patents Form 9/77)

One ✓

Request for substantive examination (Patents Form 10/77)

One ✓

Any other documents (please specify)

FS2

11.

I/We request the grant of a patent on the basis of this application.

Signature

Date

John C McKnight

John C McKnight

11 October 2002

12. Name and daytime telephone number of Person to contact in the United Kingdom

John C McKnight (01482) 583719

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

-) If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
 -) Write your answers in capital letters using black ink or you may type them.
 -) If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
 -) If you have answered 'Yes' Patents Form 7/77 will need to be filed.
 -) Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patents Office.

DUPLICATE

IMPROVEMENTS IN AND TO ORGANIC COMPOSITIONS

5

This invention relates to a pourable aqueous bleach composition which contains abrasives, suitable for use in cleaning hard surfaces such as are found, for example, in lavatories and kitchens.

- 10 It is particularly difficult to produce aqueous bleach stable, thickened abrasive cleaning compositions which offer the simultaneous benefits of: good bleach stability which provides an acceptable shelf life for a product; acceptable viscosity characteristics; relatively low cost; and of course efficacy in removing stains and in effectively disinfecting surfaces, especially on inclined hard surfaces such as tiled, enameled and porcelain surfaces such as are typically associated
- 15 with bathrooms or kitchens. While the art provides a number of such compositions directed to satisfying these requirements, these compositions have not uniformly met with success. The present invention overcomes many of these shortcomings in the prior art.

- A composition according to the invention is a stable, single phase, thickened bleach containing composition capable of adhering to vertical or inclined surfaces longer than thinner compositions. Such a composition is effective as an agent for stain and soil removal as well as disinfection. The high level of bleach stability and single solution phase behavior of the composition enables the composition to have an acceptable shelf life. The compositions exhibit little or no visibly discernible syneresis during its normal shelf life (6-9 months) and shelf life
- 25 storage conditions (20°C.). In particularly preferred embodiments the compositions exhibit little or no syneresis under accelerated aging test conditions and at the same time exhibited good bleach stability. Such is particularly important for use and storage of the product in warm climate countries (South Africa, Brazil, etc.).

- 30 The present invention provides a liquid thickened chlorine bleach composition comprising an active chlorine source;
at least one surfactant selected from anionic surfactants, amine oxides, and mixtures thereof;

at least one thickener selected from polycarboxylates, polyacrylamides, clays, gums, cellulose derivatives, and mixtures thereof;

at least one abrasive material selected from oxides, carbonates, quartzes, siliceous chalk, diatomaceous earth, colloidal silicon dioxide, alkali metasilicates, organic abrasive materials

- 5 selected from polyolefins, polyethylenes, polypropylenes, polyesters, polystyrenes, acetonitrile-butadiene-styrene resins, melamines, polycarbonates, phenolic resins, epoxies and polyurethanes, natural materials selected from rice hulls, corn cobs, and the like, nepheline syenite, or talc and mixtures thereof;
- water; and

- 10 optionally, one or more materials selected from perfumes and perfume stabilizers, builders, rheology stabilizers; pH and buffering agents, electrolytes, pigments, colorants and the like.

- Compositions according to the invention are alkaline in character, desirably having a pH of about 12 or more, exhibit very favorable viscosity characteristics, are good hard surface
- 15 cleaners and feature good bleach stability over time. The compositions may also include minor amounts, generally not more than a total of 10% wt., desirably less than 5% wt. of one or more optional constituents including ones which may improve the aesthetic appeal of the compositions, viz., perfumes and colorants. Such optional constituents should not undesirably affect the shelf stability or rheology of the compositions.

- 20 The chlorine source can be either organic or inorganic including alkali metal and alkaline earth metal hypohalites, hypohalite addition products, haloamines, haloinines, haloimides, and haloamides. These also produce hypohalous bleaching species in situ. Preferred is hypochlorite and compounds producing hypochlorite in aqueous solution, although hypobromite
- 25 is another potential halogen bleach. Those bleaching agents which yield a hypochlorite species in aqueous solution, include alkali metal and alkaline earth metal hypochlorites, hypochlorites addition products, chloramines, chlorimines, chloramides, and chlorimides. Examples of compounds of this type include sodium, potassium, lithium, and calcium hypochlorite, monobasic calcium hypochlorite, dibasic magnesium hypochlorite, chlorinated trisodium
- 30 phosphate dodecahydrate, potassium dichloroisocyanurate, sodium dichloroisocyanurate, sodium dichloroisocyanurate dihydrate, trichlorocyanuric acid, 1,3-dichloro-5,5-dimethylhydantoin, N-chlorosulfamide, Chloramine T, Dichloramine T, Chloramine B and Dichloramine B.

At lower pH levels, aqueous solutions formed by dissolving hypochlorite-yielding compounds contains active chlorine, partially in the form of hypochlorous acid moieties and partially in the form of hypochlorite ions. At pH levels above about 10, which is preferred for compositions containing hypochlorite, essentially all (greater than 99%) of the active chlorine is reported to be in the form of hypochlorite ion.

Most of the above-described hypochlorite-yielding bleaching agents are available in solid or concentrated form and are dissolved in water during preparation of the compositions of the instant invention. Some of the above materials are available as aqueous solutions.

The above-described bleaching agents are dissolved in the aqueous liquid component of the present composition and are present in an active amount of from about 0.1% to 15% available chlorine.

Compositions of the present invention also include at least one surfactant selected from anionic surfactant, amine oxides, and mixtures thereof.

Examples of anionic surfactants include, for example, alkali metal salts, ammonium salts, amine salts, or aminoalcohol salts of one or more of the following compounds (linear and secondary): alcohol sulfates and sulfonates, alcohol phosphates and phosphonates, alkyl sulfates, alkyl ether sulfates, sulfate esters of an alkylphenoxy polyoxyethylene ethanol, alkyl monoglyceride sulfates, alkyl sulfonates, olefin sulfonates, paraffin sulfonates, beta-alkoxy alkane sulfonates, alkylamidoether sulfates, alkylaryl polyether sulfates, monoglyceride sulfates, alkyl ether sulfonates, ethoxylated alkyl sulfonates, alkylaryl sulfonates, alkyl benzene sulfonates, alkylamide sulfonates, alkyl monoglyceride sulfonates, alkyl carboxylates, alkyl sulfoacetates, alkyl ether carboxylates, alkyl alkoxy carboxylates having 1 to 5 moles of ethylene oxide, alkyl sulfosuccinates, alkyl ether sulfosuccinates, alkylamide sulfosuccinates, alkyl sulfosuccinamates, octoxynol or nonoxynol phosphates, alkyl phosphates, alkyl ether phosphates, taurates, N-acyl taurates, fatty taurides, fatty acid amide polyoxyethylene sulfates, isethionates, acyl isethionates, and sarcosinates, acyl sarcosinates, or mixtures thereof. Generally, the alkyl or acyl radical in these various compounds comprise a carbon chain containing 12 to 20 carbon atoms.

Examples of the foregoing anionic surfactants are available under the following tradenames: RHODAPON, STEPANOL, HOSTAPUR, SURFINE, SANDOPAN, NEODOX, BIOSOFT, and AVANEL.

5

Amine oxide compounds which can be used in the present invention may be defined as one or more of the following of the four general classes:


(1) Alkyl di (lower alkyl) amine oxides in which the alkyl group has about 6-24, and preferably 8-18 carbon atoms, and can be straight or branched chain, saturated or unsaturated. The lower alkyl groups include between 1 and 7 carbon atoms, but preferably each include 1 - 3 carbon atoms. Examples include octyl dimethyl amine oxide, lauryl dimethyl amine oxide, myristyl dimethyl amine oxide, and those in which the alkyl group is a mixture of different amine oxides, such as dimethyl cocoamine oxide, dimethyl (hydrogenated tallow) amine oxide, and myristyl/palmityl dimethyl amine oxide;

(2) Alkyl di (hydroxy lower alkyl) amine oxides in which the alkyl group has about 6-22, and preferably 8-18 carbon atoms, and can be straight or branched chain, saturated or unsaturated. Examples include bis-(2-hydroxyethyl) cocoamine oxide, bis-(2-hydroxyethyl) tallowamine oxide; and bis-(2-hydroxyethyl) stearylamine oxide;

(3) Alkylamidopropyl di(lower alkyl) amine oxides in which the alkyl group has about 10-20, and preferably 12-16 carbon atoms, and can be straight or branched chain, saturated or unsaturated. Examples are cocoamidopropyl dimethyl amine oxide and tallowamidopropyl dimethyl amine oxide; and

(4) Alkylmorpholine oxides in which the alkyl group has about 10-20, and preferably 12-16 carbon atoms, and can be straight or branched chain, saturated or unsaturated.


While these amine oxides recited above may be used, preferred are amine oxides which may be represented by the following structural representation:




wherein

each R_1 independently is a straight chained C_1 - C_4 alkyl group; and,

R_2 is a straight chained C_6 - C_{22} alkyl group or an alkylamidoalkylene having the formula



5 where R_3 is C_5 - C_{20} alkyl or



where n is 1 to 5 and p is 1 to 6; additionally, R_2 or R_3 could be ethoxylated (1 to 10 moles EO/mol) or propoxylated (1 to 10 moles of PO/mol).

- 10 Each of the alkyl groups may be linear or branched, but most preferably are linear. Examples include Ammonyx® LO which is described to be as a 30%wt. active solution of lauryl dimethyl amine oxide; Ammonyx® CDO Special, described to be a about 30%wt. active solution of cocoamidopropylamine oxide, as well as Ammonyx® MO, described to be a 30%wt. active solution of myristyldimethylamine oxide, all available from Stepan Company (Northfield, IL) with
- 15 similar materials also available from Lonza under the Barlox trademark.

Some of the aforementioned surfactants are bleach-stable but some are not. When the composition contains a hypochlorite bleach, it is preferable that the detergent surfactant is bleach-stable. Such surfactants desirably do not contain functions such as unsaturation and

20 some aromatic, amide, aldehydic, methyl keto or hydroxyl groups which are susceptible to oxidation by the hypochlorite.

The surfactant component, selected from anionic surfactants, amine oxides, and mixtures thereof, is present in the compositions of the present invention in an amount of from about 0.1 to

25 about 10% by weight.

At least one thickener is used in the present compositions. One example of thickeners contemplated herein include organic polymeric thickeners include polycarboxylate polymers having a molecular weight from about 500,000 to about 4,000,000, preferably from about

1,000,000 to about 4,000,000, with, preferably, from about 0.5% to about 4% crosslinking.

Preferred polycarboxylate polymers include polyacrylate polymers including those sold under trade names Carbopol®, Acrysol® ICS-1 and Sokalan®. The preferred polymers are polyacrylates. Other monomers besides acrylic acid can be used to form these polymers including such monomers as ethylene and propylene which act as diluents, and maleic anhydride which acts as a source of additional carboxylic groups. Another example of polymeric based thickeners are those based on polyacrylamides. One example is Solagum from Seppic.

- 10 Another class of thickeners include colloid-forming clays, for example, such as smectite and/or attapulgite types. Inorganic colloid forming clays tend to provide higher stability in the presence of chlorine and do not thin when subjected to shear.

- 15 The clay materials can be described as expandable layered clays, i.e., aluminosilicates and magnesium silicates. The term "expandable" as used to describe the instant clays relates to the ability of the layered clay structure to be swollen, or expanded, on contact with water. The expandable clays used herein are those materials classified geologically as smectites (or montmorillonite) and attapulgites (or polygorskites).

- 20 Smectites are three-layered clays. There are two distinct classes of smectite-type clays. In the first, aluminum oxide is present in the silicate crystal lattice; in the second class of smectites, magnesium oxide is present in the silicate crystal lattice. The general formulas of these smectites are $\text{Al}_2(\text{Si}_2\text{O}_5)_2(\text{OH})_2$ and $\text{Mg}_3(\text{Si}_2\text{O}_5)(\text{OH})_2$, for the aluminum and magnesium oxide type clays, respectively. It is to be recognized that the range of the water of hydration in the above formulas may vary with the processing to which the clay has been subjected.

- 30 Commercially available clays include, for example, montmorillonite (bentonite), volchonskoite, nontronite, beidellite, hectorite, saponite, sauconite and vermiculite. The clays herein are available under various trade names such as Gelwhite H NF and Gelwhite GP from Southern Clay Products. (both montmorillonites); Van Gel O from R. T. Vanderbilt, smectites, laponites and layered silicates from Southern Clay Products.

A second type of expandable clay material useful in the instant invention is classified geologically as attapulgite (polygorskite). Attapulgites are magnesium-rich clays having principles of superposition of tetrahedral and octahedral unit cell elements different from the smectites.

Like the smectites, attapulgite clays are commercially available. For example, such clays are marketed under the tradename Attagel, i.e. Attagel 40, Attagel 50 and Attagel 150 from Engelhard Minerals & Chemicals Corporation.

0 The thickener component may be used in amounts of about 0.1 to 10 wt-%.

Another component of the present invention is at least one abrasive. Examples of abrasive materials include oxides, carbonates, quartzes, siliceous chalk, diatomaceous earth, colloidal silicon dioxide, alkali metasilicates, organic abrasive materials selected from polyolefins, 5 polyethylenes, polypropylenes, polyesters, polystyrenes, acetonitrile-butadiene-styrene resins, melamines, polycarbonates, phenolic resins, epoxies and polyurethanes, natural materials selected from rice hulls, corn cobs, and the like, nepheline syenite, or talc and mixtures thereof. The particle size of the abrasive agent can range from about 1 μm to about 1000 μm , preferably between about 10 μm to about 200 μm , and more preferably between about 10 μm and about 20 100 μm . It is preferred to use those abrasive agents that will not scratch glass or ceramic surfaces. Such abrasive agents include calcium carbonate, siliceous chalk, diatomaceous earth, colloidal silicon dioxide, sodium metasilicate, talc, and organic abrasive materials. Calcium carbonate is preferred. The amount of abrasive material can range from about 5 to about 30 wt%.

25

Examples

For purposes of illustration of the present inventive compositions, various formulations were produced and are reported below.

30

Into a suitably sized vessel, a measured amount of room temperature water ($\sim 20^\circ\text{C}$) was provided after which measured amounts of remaining constituents were added. All of the remaining constituents were similarly supplied at room temperature; mixing of the constituents

was achieved by the use of a magnetic stirrer apparatus. Mixing, which generally lasted several minutes, and maintained until the particular exemplary formulation appeared to be homogeneous.

- 5 It is to be noted that the constituents may be added in any order. In some instances, the thickener is added first and then followed by water to form a thickened system to which the other components are added and in other instances, a premix of water and thickener is made which is then added to another mixture which contains the remaining components.
- 10 Inventive formulations subject of the present application are shown in Table 1. The quantities of composition components are given as percentages by weight (wt%). Unless otherwise noted, the components in Table 1 are at 100% active. The components are described in Table 2.

Table 1						
	Ex. 1	Ex. 2	Ex. 3	Ex. 4	Ex. 5	Ex. 6
Components	Wt %	Wt %	Wt %	Wt %	Wt %	Wt %
DI Water	41.28	39.33	36.33	39.28	30.00	33.00
Carbopol 676 (1.5%)	26.67	26.67	26.67	26.67	30.00	30.00
Oxy-Rite 100	0.05			0.05	13.00	
Gelwhite H NF (5%)	10.00	10.00	10.00	10.00		10.00
Sodium Hydroxide (50%)	1.50	1.50	1.50	1.50	1.50	1.50
Sodium Hypochlorite (16%)	7.00	7.00	7.00	7.00	7.00	7.00
Calcium Carbonate	10.00	12.00	15.00	12.00	15.00	15.00
Ammonyx MO	1.00	1.00	1.00	1.00	1.00	1.00
Genopur BK	2.50	2.50	2.50	2.50	2.50	2.50
Total	100.00	100.00	100.00	100.00	100.00	100.00

15

Table 1 (cont'd)						
	Ex. 7	Ex. 8	Ex. 9	Ex. 10	Ex. 11	Ex. 12
Components	Wt %	Wt %	Wt %	Wt %	Wt %	Wt %
DI Water	23.50	42.00	43.00	39.50	43.00	33.33
Gelwhite GP (5%)	10.00	5.00	5.00	3.00	5.00	15.00
Carbopol 676 (1.5%)	42.00	33.00	30.00	35.00	33.00	26.67
Sodium Hydroxide (50%)	1.50	1.50	1.50	1.50	1.50	1.50
Sodium Hypochlorite	7.00	7.00	7.00	7.00	7.00	7.00
Calcium Carbonate	12.50	9.00	10.00	10.00	7.00	12.00
Titanium Dioxide				0.50	0.50	
Ammonyx MO	1.00	1.00	1.00	1.00	1.00	1.00
Genopur BK	2.50	1.50	2.50	2.50	2.00	3.50
Total	100.00	100.00	100.00	100.00	100.00	100.00

Table 1 (cont'd)						
	Ex. 13	Ex. 14	Ex. 15	Ex. 16	Ex. 17	Ex. 18
Components	Wt %	Wt %	Wt %	Wt %	Wt %	Wt %
DI Water	36.33	38.00	41.33	28.50	33.50	27.00
Carbopol 676 (1.5%)	26.67	30.00	26.67	45.00	40.00	30.00
Gelwhite H NF (5%)	15.00	10.00	10.00			16.00
Sodium Hydroxide (50%)	1.50	1.50	1.50	1.00	1.00	1.00
Sodium Lauryl Ether Sulfate				1.50	1.50	1.50
Sodium Carbonate						0.50
Sodium Silicate				1.00	1.00	
Sodium Hypochlorite (16%)	7.00	7.00	7.00	7.00	7.00	7.00
Calcium Carbonate	10.00	10.00	10.00	15.00	15.00	16.00
Ammonyx MO	1.00	1.00	1.00	1.00	1.00	1.00
Genopur BK	2.50	2.50	2.50			
Total	100.00	100.00	100.00	100.00	100.00	100.00

5

Table 1 (cont'd)						
	Ex. 19	Ex. 20	Ex. 21	Ex. 22	Ex. 23	Ex. 24
Components	Wt %	Wt %	Wt %	Wt %	Wt %	Wt %
DI Water	41.33	10.00	19.00	36.00	10.00	20.03
Carbopol 676 (1.5%)	26.67	30.00	54.00	35.00	10.00	26.67
Van Gel O					50.00	
Mineral Colloid BP						30.00
Laponite (4%)		37.50				
Gelwhite H NF (5%)	10.00		1.00	5.00		
Sodium Hydroxide (50%)	1.50	1.00	2.00	1.50	1.00	0.30
Sodium Carbonate		1.00			1.00	
Sodium Hypochlorite (16%)	7.00	7.00	7.00	7.00	7.00	7.00
Sodium Lauryl Ether Sulfate					1.00	1.00
Calcium Carbonate	10.00	12.00	15.00	12.00	20.00	15.00
Ammonyx MO	1.00			1.00		
Biosoft D-40		1.50	2.00			
Genopur BK	2.50			2.50		
Total	100.00	100.00	100.00	100.00	100.00	100.00

10

Table 1 (cont'd)

	Ex. 25	Ex. 26	Ex. 27	Ex. 28	Ex. 29	Ex. 30
Components	Wt %	Wt %	Wt %	Wt %	Wt %	Wt %
DI Water	36.33	33.00	33.00	50.33	20.00	17.50
Gelwhite GP (5%)	15.00	15.00	15.00			
Solagum SF 306				1.00		
Laponite (5%)					28.00	30.00
Carbopol 676 (1.5%)	26.67	30.00	30.00	26.67	30.00	30.00
Sodium Hydroxide (50%)	1.50	1.50	1.50	1.50	1.50	1.50
Sodium Hypochlorite (16%)	7.00	7.00	7.00	7.00	7.00	7.00
Calcium Carbonate	10.00	10.00	10.00	10.00	10.00	10.00
Ammonyx MO	1.00	1.00	1.00	1.00		3.50
Genopur BK			2.50			0.50
Sodium Lauryl Ether Sulfate	2.50	2.50		2.50	3.50	
Total	100.00	100.00	100.00	100.00	100.00	100.00

Table 2

DI Water	Deionized water
Carbopol 676 (1.5%)	Highly cross-linked polyacrylate polymer (Noveon; 100% active; added as 1.5% active solution in water)
Oxy-Rite 100	Aromatic based rheological stabilizer (Noveon; 100% active)
Gelwhite H NF (5%)	Montmorillonite (Southern Clay Products, Inc.; 100% active; added as 5% active solution in water)
Sodium Hydroxide (50%)	Sodium hydroxide (50% active solution in water)
Sodium Hypochlorite (16%)	Sodium hypochlorite (16% active solution in water)
Calcium Carbonate	Calcium carbonate
Ammonyx MO	Myristyldimethylamine oxide (Stepan; 30% active)
Genopur BK	Mixture of anionic surfactants (Clariant)
Gelwhite GP (5%)	Montmorillonite (Southern Clay Products, Inc.; 100% active; added as 5% active solution in water)
Titanium Dioxide	Titanium oxide
Sodium Lauryl Ether Sulfate	Sodium lauryl ether sulfate
Sodium Carbonate	Sodium carbonate
Sodium Silicate	Sodium silicate
Van Gel O	Hydrated magnesium aluminum silicate (smectite) clay (RT Vanderbilt)
Mineral Colloid BP	high purity montmorillonite (Southern Clay Products, Inc.; 100% active)
Laponite (4%); Laponite (5%)	Synthetic layered magnesium silicate (Southern Clay Products, Inc.; 100% active; added as a 4% (or 5%) active solution in water)
Biosoft D-40	Sodium linear alkylbenzene sulfonate (Stepan; 38% active)
Solagum SF 306	Polyacrylamide co-polymer (Seppic)

The compositions of the present invention are expected to have good cleaning and/or disinfecting properties as described herein.

Claims:

- 5 1. A liquid thickened chlorine bleach composition comprising:
- an active chlorine source;
at least one surfactant selected from anionic surfactants, amine oxides, and mixtures thereof;
at least one thickener selected from polycarboxylates, polyacrylamides, clays, gums, cellulose
10 derivatives, and mixtures thereof;
at least one abrasive material selected from oxides, carbonates, quartzes, siliceous chalk,
diatomaceous earth, colloidal silicon dioxide, alkali metasilicates, organic abrasive materials
selected from polyolefins, polyethylenes, polypropylenes, polyesters, polystyrenes, acetonitrile-
butadiene-styrene resins, melamines, polycarbonates, phenolic resins, epoxies and
15 polyurethanes, natural materials selected from rice hulls, corn cobs, and the like, nepheline
syenite, or talc and mixtures thereof;
water; and
optionally, one or more materials selected from perfumes and perfume stabilizers, builders,
rheology stabilizers; pH and buffering agents, electrolytes, pigments, colorants and the like.
- 20
2. The composition according to claim 1 wherein the surfactant is an amine oxide.
3. The composition according to any one of claims 1 to 2 wherein the surfactant is a
mixture of anionic surfactant and amine oxide.
- 25
4. The composition according to any one of claims 1 to 3 wherein the anionic surfactant is
selected from alkyl sulfates and alkyl ether sulfates.
5. The composition according to any one of claims 1 to 4 wherein the anionic surfactant is
30 selected from alkyl ether sulfates.
6. The composition according to any one of claims 1 to 5 wherein the thickener is a mixture
of polycarboxylates and clays.

7. The composition according to any one of claims 1 to 5 wherein the thickener is a mixture of polycarboxylates and polyacrylamides.

5 8. The composition according to any one of claims 1 to 5 wherein the thickener is a polycarboxylates.

9. The composition according to any one of claims 1 to 8 which contains a rheology modifier.

10

10. The compositions of the present invention as shown in Examples Ex. 1 to Ex. 30.

Abstract

IMPROVEMENTS IN AND TO ORGANIC COMPOSITIONS

- 5 The present invention relates to thickened liquid chlorine bleach compositions useful in the treatment of hard surfaces.

PCT Application

GB0304433

